


Item Number	Description	Quantity
1	HEAD Ø168	2
2	TUBE Ø168,3	1
3	BAFFLE	1
4	BASE SUPPORT Ø90	1
5	FILTER SUPPORT	1
6	FILTER	1
7	3/8" SAE	1
8	WELDING CONNECTION (FE) ODSØ67,4	1
9	WELDING CONNECTION (FE) ODSØ67,4	1
10	SCREW M8X25	1
11	NUT M8	1
12	FLOATING BALL	1
13	PIN	2
14	FLOAT SUPPORT	1
15	FLOAT BODY	1
16	NEEDLE	1
17	BRASS TUBE ODØ8	1
18	LABEL	1
19	PRE-CHARGE OIL LEVEL	1

INDIVIDUAL PACKING

Tolleranze di lavorazione: ISO 2768-C

Rev.	Data-Date	Dis.-Draftsman	Visto-Checked by	Descrizione Revisione - Revision Description
Denominazione - Denomination				Codice Disegno - Drawing Code
OIL.SEP.12LT.Ø168X620 ODS67 PS45BAR - OS 12-2 5/8				SOIR67168620B
PS - Design 45 BAR		PW - Work 45 BAR	PT - Test 67,5 BAR	Temperatura - Temperature -40°C +100°C
Refrigerant HFC, HCFC		Categoria PED CAT.II	 Property of OCS COLD SRL	
Scala-Scale 1:6		Data-Date 12/04/2014	Disegnatore - Draftsman G.BOKARIS	Visto-Checked by S.SPINELLO
Peso - Weight [kg] 13.17		Prodotto e Realizzato Secondo Direttiva 97/23/CE Produced and Made According to Directive 97/23/CE		
Materiale - Material		Spessore - Thickness		Colore Vernice-Painted Color RAL 3005 - RED
Cod.STD:				