



Item Number	Description	Quantity
1	HEAD Ø220	2
2	TUBE Ø219,1	1
3	BAFFLE	1
4	BASE SUPPORT Ø140	1
5	FILTER SUPPORT	1
6	FILTER	1
7	3/8" SAE	1
8	WELDING CONNECTION (FE) ODSØ67,4	2
9	SCREW TTQ M10X30	1
10	NUT M8	1
11	FLOATING BALL	1
12	PIN	2
13	FLOAT SUPPORT	1
14	FLOAT BODY	1
15	NEEDLE	1
16	BRASS TUBE ODØ8	1
17	PRE-CHARGE OIL LEVEL	1
18	LABEL	1

INDIVIDUAL PACKING

Tolleranze di lavorazione: ISO 2768-C

Rev.	Data-Date	Dis.-Draftsman	Visto-Checked by	Descrizione Revisione - Revision Description
Denominazione - Denomination				Codice Disegno - Drawing Code
OIL.SEP.20LT.Ø219X620 ODS67 PS45BAR - OS 20-2 5/8				SOIR67219620B
PS - Design		PW - Work	PT - Test	Temperatura - Temperature
45 BAR		45 BAR	67,5 BAR	-40°C +100°C
Refrigerant		Categoria PED		Rev.
HFC, HCFC		CAT.II		0
Disegnatore - Draftsman		Visto-Checked by		Peso - Weight [kg]
G.BOKARIS		S.SPINELLO		18.30
Materiale - Material		Spessore - Thickness		Prodotto e Realizzato Secondo Direttiva 97/23/CE
				Produced and Made According to Directive 97/23/CE
Colore Vernice-Painted Color		Codice STD		
RAL 3005 - RED				

